



20 bar
operating pressure

167 l/h
drain capacity

1/2"
connections

1,5 to 65 °C
operating temperature range

DESCRIPTION

AOK 20B has been developed for fully automatic discharging of condensate or any other non-aggressive fluid from compressed air system. For any other technical gas please contact producer or your local distributor.

The unit can be installed as external drain on any application specified. Condensate accumulates in the aluminium reservoir and when the level is high enough condensate is discharged from the system without any air losses. Direct acting valve is operated by precise level controlled floater which assures reliable and efficient operation. Thanks to robust aluminium housing AOK 20B is suitable for heavy duty applications. AOK 20B is also equipped with separate manual drain for venting.

AOK 20B can be used in variety of applications. For applications not listed please contact producer or your local distributor

AOK 20B SERIES

AUTOMATIC MECHANICAL CONDENSATE DRAIN



| TECHNICAL DATA | AOK 20B |
|---------------------------------------|------------------------------|
| Operating temperature range | 1,5 - 65 °C (35-149 °F) |
| Operating pressure | 20 bar (290 psi) |
| Mass | 0,6 kg |
| Discharge capacity (at 7 bar/101 psi) | 167 l/h |
| Inlet connection | G 1/2" (NPT option) |
| Outlet connection | G 1/2" (NPT option) |
| Dimensions A × B × C | 135 × 110 × 130 mm |
| Medium | Condensate (air, water, oil) |

RECOMMENDATIONS

Install ball valve between pressure vessel and inlet connection.
Install strainer element between pressure vessel and inlet connection.
Install nipple with venting tube to avoid generating of air bubbles.
Screw nipple in inlet connection.

APPLICATIONS

- Air compressor (piston or screw)
- After-cooler
- Cyclone condensate separator
- Pressure vessel/Air tank
- Air dryer
- Air filter

